

**Products** Attachments for Frontloader with quick coupler, Frontloader without quick coupler

**Pic. 204 Silage fork with grapple**

for tractors



opened

**Standard equipment:**

- For frontloaders with EURO-coupler
- Thick material main tubes with welded cones
- High value full material tines, 800mm length
- Twist protected tines in the grapple
- With 2 hydraulic cylinders
- Opening width ca. 1200mm

Special designed attachments are deliverable on request !

Width	Volume	Weight	Tines
1300 mm	ca. 1050 l	ca. 310 kg	7 x normal load
1500 mm	ca. 1220 l	ca. 360 kg	8 x normal load
1700 mm	ca. 1380 l	ca. 410 kg	9 x normal load
1900 mm	ca. 1540 l	ca. 460 kg	10 x normal load
2100 mm	ca. 1700 l	ca. 510 kg	11 x normal load
2300 mm	ca. 1860 l	ca. 560 kg	12 x normal load
1300 mm	ca. 1050 l	ca. 325 kg	7 x heavy duty
1500 mm	ca. 1220 l	ca. 380 kg	8 x heavy duty
1700 mm	ca. 1380 l	ca. 430 kg	9 x heavy duty
1900 mm	ca. 1540 l	ca. 480 kg	10 x heavy duty
2100 mm	ca. 1700 l	ca. 535 kg	11 x heavy duty
2300 mm	ca. 1860 l	ca. 585 kg	12 x heavy duty

**Additional:**

- Model with 1 bowed tine 600mm at every side
- Model with hydr. push off wall till 1700mm width (1x DA needed)
- Model with hydr. push off wall above 1700mm width (1x DA needed)
- Model with switch valve 12V / 90l in connection with push off wall
- Model with automatic switch valve
- Model for frontloader without EURO - couplingsystem