

**Products** Attachments for Frontloader with quick coupler, Frontloader without quick coupler

**Pic. 218 Silagebucket type S**

for traktors



Opened



With Adapter on Weidemann telehandler



The Silagebucket is designed for collection and transportation of silage of each kind in agriculture range.

**Standard equipment:**

- For frontloaders with EURO-coupler
- With highwear resistant cutting edge (150x20mm, 500 HB)
- With strong substructure
- Bucket height 650mm, bucket depth 850mm
- With 2 hydraulic cylinders
- Opening width ca. 1250mm
- To 2000mm width with 1 sickle reinforcement above 2000mm width with 2 sickle reinforcements

The width 1650mm can only be used on EURO-couplers with central locking system.

Special designed attachments are deliverable on request !

Width	Volume	Sickle tines	Bearing points	Weight
1650 mm	ca. 840 l	5	2	ca. 555 kg
1800 mm	ca. 925 l	5	2	ca. 580 kg
2000 mm	ca. 1040 l	5	2	ca. 630 kg
2200 mm	ca. 1140 l	6	4	ca. 665 kg
2400 mm	ca. 1250 l	6	4	ca. 710 kg
2600 mm	ca. 1350 l	7	4	ca. 755 kg
2800 mm	ca. 1440 l	7	4	ca. 800 kg

**Additional:**

Model with removable sideparts (screwed)

Model with raised sideparts (convex, screwed)

Model with stronger cutting edge (200x20mm, 500HB) per m.

Model with high wear res. substrc. & screwed knife (dbl. Beveled, 500HB) per m.

Model with high tip function (+ 350kg, + 1x DA needed)

Model with switch valve 12V / 90l in connection with high tip function

Model for frontloader without EURO - couplingsystem