

Products Attachments for Frontloader with quick coupler, Frontloader without quick coupler

Pic. 221 Silagecutter type C

for traktors



Model with heavy duty tines

The Silagecutter is designed for clean silage cutting of each kind in agriculture range.

Standard equipment:

- For 3-point tail hydraulics
- Extrem robustly constructed
- Thick material main tube with welded cones
- High value full material tines, 800mm length
- Big dimensioned hydraulic cylinders
- 90l/min oil flow divider
- With latticed back part (height 1200mm)
- Optional with waved, edged or smooth knife (screwed)
- Opening width ca. 12000mm

Type	Volume	Blockdimensions	Weight	Cylinders
C157	ca. 1400 l	157x120x75cm	ca. 1050 kg	2
C178	ca. 1600 l	178x120x75cm	ca. 1180 kg	2
C199	ca. 1780 l	199x120x75cm	ca. 1300 kg	2

Additional:

- Model with heavy duty tines for type C157
- Model with heavy duty tines for type C178
- Model with heavy duty tines for type C199
- Model with hydraulic push off wall for C-Serie (+1 x DA needed)
- Model with electric switch valve 12V / 90l
- Model with lifting device 1000mm extra height (+1 x SA needed, 280kg)
- Model with lifting device 2000mm extra height (+1 x SA needed, 440kg)
- Model with hydraulic controlblock 90l/min (1 x SA + 2 x DA)