


Products Attachments for Front hydraulics, Tail hydraulics

Pic. 222 Silagecutter type B

for traktors



Special equipment: Lifting device and push off (For silage stock with ca. 3,5m height)



Beginning from above:
 Waved, edged and smooth knife



Special equipment: Hydraulic push off wall

The Silagecutter is designed for clean silage cutting of each kind in agriculture range.

Standard equipment:

- For 3-point tail hydraulics
- Thick material main tube with welded cones
- High value full material heavy duty tines, 1000mm length
- With 2 big dimensioned hydraulic cylinders
- 90l/min oil flow divider
- Opening width ca. 1300mm
- Optional with waved, edged or smooth knife (screwed)

Type	Volume	Blockdimensions	Weight	Cylinders
B157	ca. 1940 l	157x130x95cm	ca. 1100 kg	2
B178	ca. 2200 l	178x130x95cm	ca. 1190 kg	2
B199	ca. 2460 l	199x130x95cm	ca. 1280 kg	2

Additional:

- Model with hydraulic push off wall for B157 (+1 x DA needed, ca. 300kg)
- Model with hydraulic push off wall for B178 (+1 x DA needed, ca. 320kg)
- Model with hydraulic push off wall for B199 (+1 x DA needed, ca. 340kg)
- Model with lifting device 2000mm extra height (+1 x SA needed, 440kg)
- Model with hydraulic controlblock 90l/min (1 x SA + 2 x DA)