

Products Attachments for Frontloader with quick coupler, Frontloader without quick coupler

Pic. 234 Multipurpose bucket (4 in 1)

for traktors



Opened



The multipurpose bucket offers a lot of applications:

- Loading, like with a normal bucket
- Unloading / dispensing without dumping the bucket
- Dozing work with opened bucket
- Collection of rest material
- Grabbing of f.E. curbs

Standard equipment:

- For frontloaders with EURO-coupler
- With highwear resistant cutting edge (150x20mm, 500 HB)
- Bucket height 750mm, bucket depth 650mm
- With spill guard
- With 2 hydraulic cylinders
- 45l/min oil flow divider
- Opening width ca. 670mm

- The width 1600mm can only be used on EURO-couplers with central locking system.

Special designed attachments are deliverable on request !

Width	Volume (theo.)	Weight
1600 mm	ca. 380 l (ca. 0,50m ³)	ca. 370 kg
1800 mm	ca. 430 l (ca. 0,56m ³)	ca. 400 kg
2100 mm	ca. 500 l (ca. 0,65m ³)	ca. 450 kg
2300 mm	ca. 550 l (ca. 0,71m ³)	ca. 500 kg
2500 mm	ca. 575 l (ca. 0,75m ³)	ca. 525 kg
2500 mm	ca. 600 l (ca. 0,78m ³)	ca. 550 kg

Additional:

- Model with sticked gravel tines per piece
- Model with protection tube
- Model for frontloader without EURO - couplingsystem