

Products Attachments for Front hydraulics, Tail hydraulics

Pic. 240 Dozerblade type HPH

for traktors



Side blade right / flappable ripper



Flappable ripper



With elektro-hydraulic valve

This dozerblade type HPH is designed for road building and maintenance in agriculture branch. The blade can be pushed and also pulled.

The tilt function allows building of profiles on the roads. The blade can be shifted sideways. All functions can be adjusted hydraulically.

Standard equipment:

- For 3-point front and tail hydraulics
- Mechanically turnable for 360°
- Hydraulic turnable +/- 30° in the adjusted position
- With screwed cutting edge out of highwear resistant steel (150x20mm, 500HB)
- With preparation for additional extensions or side blades
- Height 550mm
- Hydraulically pivotable to the side for 800mm left and right
- Hydraulically vertical turnable up to 25°
- With 2 air filled wheels, hydraulically adjustable
- (4 x DA Hydraulic functions needed)

Special designed attachments are deliverable on request !

Width	Weight
2250 mm	ca. 1180 kg
2500 mm	ca. 1215 kg
2750 mm	ca. 1250 kg
3000 mm	ca. 1285 kg

Additional:

Model with 6 flapable rippers	
Model with 500mm extension -screwed	per piece
Model with side blade left or right	per piece
Model with positioning lights	
Model with elektro-hydraulic controlblock 4xDA	