

**Products** Attachments for Front hydraulics, Frontloader with quick coupler, Frontloader without quick coupler, Tail hydraulics

**Pic. 241 Snowclearing- and dozerblade type SPS**

for traktors



Rearward view: Special equipment: Hydraulic turnable, special rubber blade



Model hydr. turnable, rubberblade and level compensation



Special equipment: Rubber blade

This blade is designed for simple dozing works and can also be used for snowclearing work on plain grounds.

**Standard equipment:**

- Optional for frontloaders with EURO-coupler, front and tail hydraulics, lifting triangle and communal connection plate on tractors
- Mechanically turnable for 30° left and right
- Height 750mm, with hardened cutting edge (100 x 16mm)

Special designed attachments are deliverable on request !

Type	Width	Workingwidth (on 30°)	Weight
SPS 16	1600 mm	ca. 1350 mm	ca. 235 kg
SPS 18	1800 mm	ca. 1500 mm	ca. 265 kg
SPS 20	2000 mm	ca. 1700 mm	ca. 290 kg
SPS 22	2200 mm	ca. 1850 mm	ca. 320 kg
SPS 24	2400 mm	ca. 2000 mm	ca. 350 kg
SPS 28	2800 mm	ca. 2350 mm	ca. 410 kg
SPS 30	3000 mm	ca. 2500 mm	ca. 440 kg
SPS 32	3200 mm	ca. 2700 mm	ca. 470 kg

**Additional:**

Model hydr. turnable (le. + ri. 35°) incl. shockvalve

Model with tissued special rubber blade (150x40mm)

per m.

Model with positioning lights and warn flags

Model for frontloader without EURO - couplingsystem