

**Products** Attachments for Front hydraulics, Frontloader with quick coupler, Frontloader without quick coupler, Tail hydraulics

**Pic. 242 Snow blade type SRS**

for traktors



The Snow blade is designed to clean up low till middle snow heights on parking lots and streets.

**Standard equipment:**

- Optional for frontloaders with EURO-coupler, front and tail hydraulics, lifting triangle and communal connection plate on tractors
- Shield height 800mm (middle) and ca. 930mm (outsided)
- With flapable cutting edge staffed with a special-rubber-blade (150x40mm)
- Hydraulic adjustable 30° left and right
- With level adjustment (turnable beared +/-15°)
- With 2 stepless adjustable rubber tires (max. speed 30km/h)
- With lights and warnflags

Special designed attachments are deliverable on request !

Type	Width	Workingwidth (on 30°)	Weight
SRS 24	2400 mm	ca. 2000 mm	ca. 545 kg
SRS 28	2800 mm	ca. 2350 mm	ca. 590 kg
SRS 32	3200 mm	ca. 2700 mm	ca. 640 kg

**Additional:**

- Model with rubber blade reinforced with korund per m.
- Model with spray protection per m.
- Model with level compensation
- Model like before but incl. hydraulic lift (+1 x DA needed)
- Model for frontloader without EURO - couplingsystem