

Products Attachments for Front hydraulics, Frontloader with quick coupler, Frontloader without quick coupler, Tail hydraulics, Court loader

Pic. 243 Vario snow plough Type SPF



Special equipment: Without Special-rubber-blade

The Vario snow plough is designed to clean up low till middle snow heights on parking lots and streets.

Standard equipment:

- Optional for frontloaders with EURO-coupler, front and tail hydraulics, lifting triangle and communal connection plate on tractors
- Each blade half is singularly hydraulic turnable for +/- 35° (2xDA needed)
- With flapable cutting edge staffed with Special-rubber-blade (150x40mm)
- With level adjustment (turnable +/-15°)

Only Type SPF 16 and SPF 20:

With 2 stepless adjustable gliding skids

Only Type SPF 24 and SPF 28:

With 2 stepless adjustable rubber tires (max. speed 30km/h)

Special designed attachments are deliverable on request !

Possible work positions:



Type	Width	Working width	Shield height	Weight
SPF 16	1600 mm	ca. 1420 mm	ca. 650/800mm	ca. 315 kg
SPF 20	2000 mm	ca. 1750 mm	ca. 650/800mm	ca. 360 kg
SPF 24	2400 mm	ca. 2080 mm	ca. 875/1025 mm	ca. 435 kg
SPF 28	2800 mm	ca. 2400 mm	ca. 875/1025 mm	ca. 480 kg

Additional:

Model with rubber blade reinforced with korund per m.

Model with level compensation

Model like before but incl. hydraulic lift (+ 1xDA needed)

Model with positioning lights and warn flags

Model for frontloader without EURO - couplingsystem