

Products Attachments for Fork truck

Pic. 503 Fork truck bucket

for fork lift trucks



Transport position



Dumped



Standard equipment:

- For fork lift trucks - connected to the pallet fork carrier
 (ISO FEM II - 407mm height of pallet fork carrier or
 ISO FEM III - 508mm height of pallet fork carrier)
- With highwear resistant cutting edge (150x20mm, 500HB)
- With strong substructure
- With 2 hydraulic cylinders
- Own gravity center [ESP] and gravity center of loading goods [LSP]
 please find in the chart

Special designed attachments are deliverable on request !

Width	Height	Depth	Volume	Weight	ESP/LSP
1300 mm	800 mm	1100 mm	650 l	580 kg	ca. 340/550 mm
1500 mm	1000 mm	1300 mm	1100 l	620 kg	ca. 390/590 mm
1800 mm	1000 mm	1300 mm	1300 l	680 kg	ca. 410/590 mm
2000 mm	1000 mm	1300 mm	1450 l	720 kg	ca. 420/590 mm

Additional:

- Model with high wear res. substrc. & cutting edge (200x20mm, 500 HB) per m.
- Model with high wear res. substrc. & screwed knife (dbl. beveled, 500 HB) per m.
- Model with quick coupling system (shiftable brackets)
- Model with combined ISO FEM II and ISO FEM III brackets
- Model with ISO FEM IV brackets (height of pallet fork carrier 635mm)
- Model with rounded edges
- Model with higher bucket sideparts (convex formed)