

Products Attachments for Fork truck

Pic. 504 Fork truck bucket - heavy duty

for fork lift trucks



Transport position



Dumped



Standard equipment:

- For fork lift trucks - connected to the pallet fork carrier (ISO FEM II - 407mm height of pallet fork carrier or ISO FEM III - 508mm height of pallet fork carrier)
- With reinforced body, cylinders and frame for heavy duty usage
- With high wear resistant substructure and cutting edge (200x20mm, 500HB)
- With 2 hydraulic cylinders
- Own gravity center [ESP] and gravity center of loading goods [LSP] please find in the chart

Special designed attachments are deliverable on request !

Width	Height	Depth	Volume	Weight	ESP/LSP
1300 mm	1100 mm	1400 mm	1150 l	640 kg	ca. 460/780 mm
1600 mm	1100 mm	1400 mm	1420 l	700 kg	ca. 480/780 mm
1800 mm	1100 mm	1400 mm	1600 l	740 kg	ca. 490/780 mm
2000 mm	1100 mm	1400 mm	1770 l	780 kg	ca. 500/780 mm
2300 mm	1100 mm	1400 mm	2050 l	840 kg	ca. 520/780 mm
2500 mm	1100 mm	1400 mm	2220 l	900 kg	ca. 530/780 mm
2800 mm	1100 mm	1400 mm	2500 l	970 kg	ca. 550/780 mm
2800 mm	1300 mm	1600 mm	3300 l	1080 kg	ca. 640/880 mm

Additional:

- Model with screwed knife (double beveled, 500HB) per m.
- Model with quick coupling system (shiftable brackets)
- Model with combined ISO FEM II and ISO FEM III brackets
- Model with ISO FEM IV brackets (height of pallet fork carrier 635mm)
- Model with rounded edges
- Model with higher bucket sideparts (convex formed)