

Products Attachments for Wheel loader, Telescopic loader

Pic. 602 Heavy duty bucket

for wheel and telescopic loaders



Model with gravel tines



Standard equipment:

- For wheel- and telescopic loader
- With highwear resistant cutting edge (150x20mm, 500HB)
- With strong substructure
- Bucket height 920mm, bucket depth 1050mm
- With spill guard
- Mit 1 respec. 2 sickle reinforcements

Special designed attachments are deliverable on request !

Width	Volume	Weight
1600 mm	ca. 850 l	ca. 430 kg
1800 mm	ca. 960 l	ca. 480 kg
2000 mm	ca. 1060 l	ca. 530 kg
2200 mm	ca. 1160 l	ca. 585 kg
2300 mm	ca. 1220 l	ca. 620 kg
2400 mm	ca. 1280 l	ca. 645 kg
2500 mm	ca. 1330 l	ca. 665 kg
2600 mm	ca. 1380 l	ca. 690 kg
2800 mm	ca. 1480 l	ca. 740 kg

Additional:

Model with high wear res. substruc. and cutting edge (200x20mm, 500HB)	per m.
Model with high wear res. substruc. and cutting edge (300x30mm, 500HB)	per m.
Model with high wear res. substruc. & screwed knife (dbl. beveled, 500HB)	per m.
Model with sticked gravel tines	per piece
Model with sticked gravel tines (heavy duty)	per piece
Model with protection tube	
Model with rearward cutting edge	per m.