

**Products** Attachments for Wheel loader, Telescopic loader

**Pic. 604 Silage fork with grapple**

for wheel and telescopic loaders



Opened



Transport of square bales



**Standard equipment:**

- For wheel- and telescopic loader
- Thick material main tubes with welded cones
- High value full material tines, 1000mm length
- Twist protected tines in the grapple
- With 2 hydraulic cylinders (Max. hydraulic pressure 220 bar)
- Opening width ca. 1300mm

Special designed attachments are deliverable on request !

Width	Volume	Weight	Tines
<b>Model with heavy duty tines</b>			
1700 mm	ca. 1700 l	ca. 560 kg	9
1900 mm	ca. 1900 l	ca. 590 kg	10
2100 mm	ca. 2100 l	ca. 620 kg	11
2300 mm	ca. 2300 l	ca. 650 kg	12
2500 mm	ca. 2500 l	ca. 680 kg	13
<b>Model with normal load tines</b>			
1700 mm	ca. 1700 l	ca. 530 kg	9
1900 mm	ca. 1900 l	ca. 560 kg	10
2100 mm	ca. 2100 l	ca. 585 kg	11
2300 mm	ca. 2300 l	ca. 610 kg	12
2500 mm	ca. 2500 l	ca. 640 kg	13

**Additional:**

Model with 1 bowed tine 600mm at every side

Model with hydr. push off wall till 1900mm width (+1 x DA needed)

Model with hydr. push off wall über 1900mm width (+1 x DA needed)

Model with switch valve 12V / 90l in connection with push off wall

Model with switch valve 12V / 120l in connection with push off wall

Model with automatic switch valve

Model with pressure holding valve (needed for as example Bobcat, Dieci, Faresin, Merlo, MF)

Model with pressure limiting valve (adjusted to 220 bar)