

Products Attachments for Wheel loader, Telescopic loader

Pic. 605 Silage fork with grapple XL

for wheel and telescopic loaders



Special equipment:
 Push off wall

Standard equipment:

- For wheel- and telescopic loader
- Thick material main tubes with welded cones
- High value heavy duty material tines, 1250mm length
- Twist protected tines in the grapple
- With 2 tines at every side
- With 2 hydraulic cylinders
 (Max. hydraulic pressure 220 bar)
- Opening width ca. 1700mm
- With latticed back part

Special designed attachments are deliverable on request !

Width	Volume	Weight	Tines
2100 mm	ca. 2750 l	ca. 980 kg	11
2300 mm	ca. 3000 l	ca. 1050 kg	12
2500 mm	ca. 3250 l	ca. 1120 kg	13
2700 mm	ca. 3500 l	ca. 1190 kg	14
2900 mm	ca. 3750 l	ca. 1260 kg	15

Additional:

- Model with hydr. push off wall till 2300mm width (+1 x DA needed)
- Model with hydr. push off wall above 2300mm width (+1 x DA needed)
- Model with switch valve 12V / 90l in connection with push off wall
- Model with switch valve 12V / 120l in connection with push off wall
- Model upper switch valve with 24V magnet
- Model with automatic switch valve
- Model with pressure holding valve (needed for as example Bobcat, Dieci, Faresin, Merlo, MF)
- Model with pressure limiting valve (adjusted to 220 bar)