

**Products** Attachments for Wheel loader, Telescopic loader

**Pic. 607 High tip bucket**

for wheel and telescopic loaders



A High tip bucket raises the unload height and the dumping angle. The Unload height will be raised for approx. 400mm over the height of the bearing point of the quick coupler.

**Standard equipment:**

- For wheel- and telescopic loader
- Qualified for loading of pour loading goods with max. 900kg/m<sup>3</sup>
- With highwear resistant cutting edge (150x20mm, 500HB)
- With strong substructure
- With 2 hydraulic cylinders (Max. hydraulic pressure 220 bar)
- With enlarged tipping angles for bigger dumping high

Special designed attachments are deliverable on request !

Width	Height	Depth	Volume (SAE)	Weight
1400 mm	900 mm	1200 mm	ca. 790 l (ca. 0,95 m <sup>3</sup> )	ca. 480 kg
1600 mm	900 mm	1200 mm	ca. 910 l (ca. 1,10 m <sup>3</sup> )	ca. 515 kg
1800 mm	900 mm	1200 mm	ca. 1020 l (ca. 1,22 m <sup>3</sup> )	ca. 550 kg
2000 mm	900 mm	1200 mm	ca. 1130 l (ca. 1,36 m <sup>3</sup> )	ca. 585 kg
1800 mm	1100 mm	1300 mm	ca. 1350 l (ca. 1,62 m <sup>3</sup> )	ca. 730 kg
2000 mm	1100 mm	1300 mm	ca. 1500 l (ca. 1,80 m <sup>3</sup> )	ca. 805 kg
2200 mm	1100 mm	1300 mm	ca. 1650 l (ca. 1,98 m <sup>3</sup> )	ca. 890 kg
2400 mm	1100 mm	1300 mm	ca. 1800 l (ca. 2,15 m <sup>3</sup> )	ca. 970 kg
2600 mm	1100 mm	1300 mm	ca. 1950 l (ca. 2,35 m <sup>3</sup> )	ca. 1050 kg

**Additional:**

- Model with high wear res. substruc. and cutting edge (200x20mm, 500HB) per m.
- Model with high wear res. substruc. & screwed knife (dbl. beveled, 500HB) per m.
- Model with screwed polyurethane cutting edge per m.
- Model with raised sideparts (convex)
- Model with pressure holding valve (needed for as example Bobcat, Dieci, Faresin, Merlo, MF)
- Model with pressure limiting valve (adjusted to 220 bar)