

Products Attachments for Wheel loader, Telescopic loader

Pic. 616 Silagebucket type S

for wheel and telescopic loaders



Special equipment:
Screwed knife

The Silagebucket is designed for collection and transportation of silage of each kind in agriculture range.

Standard equipment:

- For wheel- and telescopic loader
- With 2 hydraulic cylinders (Max. hydraulic pressure 220 bar)
- With 1 respectively 2 sickle reinforcement
- With highwear resistant cutting edge (150x20mm, 500HB)
- With strong substructure
- Bucket height 650mm, bucket depth 850mm
- Opening width ca. 1250mm

Special designed attachments are deliverable on request !

IMPORTANT: Please be informed that the opened grapple in back rolled position may crash with the lifting arm of the carrier vehicle (especially wheel loader with Z-kinematics).

For these damages we won't take any liability!

Width	Volume	Sickle tines	Bearings	Weight
1650 mm	ca. 840 l	4	2	ca. 595 kg
1800 mm	ca. 925 l	5	2	ca. 620 kg
2000 mm	ca. 1040 l	5	2	ca. 670 kg
2200 mm	ca. 1140 l	6	4	ca. 705 kg
2400 mm	ca. 1250 l	6	4	ca. 750 kg
2600 mm	ca. 1350 l	7	4	ca. 795 kg
2800 mm	ca. 1440 l	7	4	ca. 840 kg

Additional:

Model with removable sideparts (screwed)

Model with raised sideparts (screwed)

Model with high wear res. substruc. and cutting edge (200x20mm, 500HB) per m.

Model with high wear res. substruc. & screwed knife (dbl. beveled, 500HB) per m.

Model with high tip function (+ 350kg, + 1x DA needed)

Model with switch valve 12V / 90l in connection with high tip function

Model with pressure holding valve (needed for as example Bobcat, Dieci, Faresin, Merlo, MF)

Model with pressure limiting valve (adjusted to 220 bar)2