

**Products** Attachments for Wheel loader, Telescopic loader

**Pic. 620 Silagebucket type A XXL**

for wheel and telescopic loaders



Special equipment:  
 Screwed knife

The Silagebucket is designed for collection and transportation of chopped silage of each kind in agriculture range.

**Standard equipment:**

- For wheel- and telescopic loader
- Reinforced body
- With high wear resistant substructure and cutting edge (200x20mm, 500HB)
- Bucket height 1200mm, bucket depth 1200mm
- Mit 2 sickle reinforcements
- With 2 hydraulic cylinders (Max. hydraulic pressure 220 bar)
- Opening width ca. 2000mm
- Thick material main tube with welded cones
- With additional cones in the grapple for individual adjustment to different types of silage
- With 3 tines at every side

Special designed attachments are deliverable on request !

Width	Volume	Weight	Tines
2400 mm	ca. 3450 l	ca. 1590 kg	10
2600 mm	ca. 3750 l	ca. 1690 kg	12
2800 mm	ca. 4000 l	ca. 1780 kg	13
3000 mm	ca. 4250 l	ca. 1880 kg	14

**Additional:**

Model with raised sideparts (convex form, screwed)

Model with high wear resistant cutting edge (300x30mm, 500HB) per m.

Model with high wear resistant screwed knife (dbl. beveled, 500HB) per m.

Model with pressure holding valve (needed for as example Bobcat, Dieci, Faresin, Merlo, MF)

Model with pressure limiting valve (adjusted to 220 bar)