

**Products** Attachments for Wheel loader, Telescopic loader

**Pic. 622 Silagecutter type C**

for wheel and telescopic loaders



Model with heavy duty tines

The Silagecutter is designed for clean silage cutting of each kind in agriculture range.

**Standard equipment:**

- For wheel- and telescopic loader
- Thick material main tube welded cones
- High value full material tines, 800mm length
- 90l/min oil flow divider
- With latticed back part (1200mm height)
- Optional with waved, edged or smooth knife (screwed)
- Opening width ca. 1200mm
- Max. hydraulic pressure 220 bar

Type	Volume	Blockdimensions	Cylinders	Weight
C157	ca. 1400 l	157x120x75cm	2	ca. 1050 kg
C178	ca. 1600 l	178x120x75cm	2	ca. 1180 kg
C199	ca. 1780 l	199x120x75cm	2	ca. 1300 kg

**Additional:**

- Model with heavy duty tines for type C157
- Model with heavy duty tines for type C178
- Model with heavy duty tines for type C199
- Model with hydraulic push off wall for C-Serie (+1 x DA needed)
- Model with switch valve 12V/90l in connection with hydraulic push off wall
- Model with switch valve 12V/120l in connection with hydraulic push off wall
- Model with switch valve 12V/180l in connection with hydraulic push off wall
- Model above switch valve with 24V magnet
- Model with 150 l/min oil flow divider
- Model with pressure holding valve (needed for as example Bobcat, Dieci, Faresin, Merlo, MF)
- Model with pressure limiting valve (adjusted to 220 bar)