

**Products** Attachments for Wheel loader, Telescopic loader

**Pic. 623 Silagecutter type B**

for wheel and telescopic loaders



Starting from above: Waved, edged and smooth knife



Type B199 -waved knife

The Silagecutter is designed for clean silage cutting of each kind in agriculture range.

**Standard equipment:**

- For wheel- and telescopic loader
- Thick material main tube with welded cones
- High value full material heavy duty tines, 1000mm length
- 90l/min oil flow divider
- Opening width ca. 1300mm
- Optional with waved, edged or smooth knife (screwed)
- Max. hydraulic pressure 220 bar

Type	Volume	Blockdimensions	Weight	Cylinders
B157	ca. 1940 l	157x130x95cm	ca. 1100 kg	2
B178	ca. 2200 l	178x130x95cm	ca. 1260 kg	2
B199	ca. 2460 l	199x130x95cm	ca. 1350 kg	2

**Additional:**

- Model with hydr. push off wall B157 (+1 x DA needed, ca. 300kg)
- Model with hydr. push off wall B178 (+1 x DA needed, ca. 320kg)
- Model with hydr. push off wall B199 (+1 x DA needed, ca. 340kg)
- Model with switch valve 12V/90l in connection with push off wall
- Model with switch valve 12V/120l in connection with push off wall
- Model with switch valve 12V/180l in connection with push off wall
- Model above switch valve with 24V magnet
- Model with 150 l/min oil flow divider
- Model with 200 l/min oil flow divider
- Model with pressure holding valve (needed for as example Bobcat, Dieci, Faresin, Merlo, MF)
- Model with pressure limiting valve (adjusted to 220 bar)