

Products Attachments for Wheel loader, Telescopic loader

Pic. 639 Working platform BLA I and II

for wheel- and telescopic loaders - according to EU-Directive 2006/42/EG



BLA II with wooden edge guard



BLA I

Now with CE-precertification!

Standard equipment:

- For wheel- and telescopic loader
- With lockable door
- Precertificated according to EU-Directive 2006/42/EG
- **BLA I:** Width 1300mm, depth 860mm, height 1100mm
- Type test certificate no. ZP/C018/11
- **BLA II:** Width 2400mm, depth 1000mm, height 1100mm
- Lifting capacity 250kg (2 persons + tools)
- Type test certificate no. ZP/C088/11

The loader must fulfill:

- Save stand
- Automatic parallel lift function
- Deactivated tipping function
- Throttled lift function
- Pipe burst security valve on lifting cylinders
- Max. lifting height 10m
- Emergency lowering of the lifting arm when lifting height is more than 7,5m

Important: Not in our precertification listed loaders must be checked by the Notified body. This will cause extra costs. The documentation is actually only in german. Please get in contact with us.

Type	Weight
BLA I	ca. 225 kg
BLA II	ca. 480 kg

Additional:

- Model with wooden edge guard for BLA I (wood 35x55mm)
- Model with wooden edge guard for BLA II (wood 35x55mm)
- Model with screwed upper squeeze guard for BLA I
- Model with screwed upper squeeze guard for BLA II