

**Products** Attachments for Wheel loader, Telescopic loader

**Pic. 641 Vario snow plough type SPF**

for wheel- and telescopic loaders



Model without rubber blade



The Vario snow plough is designed to clean up low till middle snow heights on parking lots and streets.

**Standard equipment:**

- For wheel- and telescopic loader
- Each blade half is singularly hydraulic turnable for +/- 35° (2xDA needed)
- With flapable cutting edge staffed with Special-rubber-blade (150x40mm)
- With level adjustment (turnable +/-15°)

Only Type SPF 16 and SPF 20:

With 2 stepless adjustable gliding skids

Only Type SPF 24 and SPF 28:

With 2 stepless adjustable rubber tires (max. speed 30km/h)

Special designed attachments are deliverable on request !

**Possible work positions:**



| Type   | Width   | Working width | Shield height     | Weight     |
|--------|---------|---------------|-------------------|------------|
| SPF 16 | 1600 mm | ca. 1420 mm   | ca. 650 / 800mm   | ca. 315 kg |
| SPF 20 | 2000 mm | ca. 1750 mm   | ca. 650 / 800mm   | ca. 360 kg |
| SPF 24 | 2400 mm | ca. 2080 mm   | ca. 875 / 1025 mm | ca. 435 kg |
| SPF 28 | 2800 mm | ca. 2400 mm   | ca. 875 / 1025 mm | ca. 480 kg |

**Additional:**

Model with rubber blade reinforced with korund

per m.

Model with level compensation

Model with positioning lights and warn flags

Model with pressure holding valves (needed for as example Bobcat, Dieci, Faresin, Merlo, MF)