

Products Attachments for Wheel loader, Telescopic loader

Pic. 642 Snowclearing- and dozerblade type SPS

for wheel- and telescopic loaders



Rearwards view:- Model with hydraulic turn function and special rubber blade



Model hydr. turnable, rubberblade and level compensation



Special equipment: Rubber blade

This blade is designed for simple dozing works and can also be used for snowclearing work on plain grounds.

Standard equipment:

- For wheel- and telescopic loader
- Mechanicly turnable for 30° left and right
- Height 750mm, with hardened cutting edge (100 x 16mm)

Special designed attachments are deliverable on request !

Type	Width	Workingwidth (on 30)	Weight
SPS 20	2000 mm	ca. 1700 mm	ca. 335 kg
SPS 22	2200 mm	ca. 1850 mm	ca. 365 kg
SPS 24	2400 mm	ca. 2000 mm	ca. 395 kg
SPS 28	2800 mm	ca. 2350 mm	ca. 450 kg
SPS 30	3000 mm	ca. 2500 mm	ca. 480 kg
SPS 32	3200 mm	ca. 2700 mm	ca. 510 kg

Additional:

Model hydr. turnable (le. + ri. 35°) incl. shockvalve

Model with tissued special rubber blade (150x40mm) per m.

Model with level compensation (incl. 2 rubber tires / max. 30km/h)

Model with pressure holding valve (needed for as example Bobcat, Dieci, Faresin, Merlo, MF)

Model with pressure limiting valve (adjusted to 220 bar)