



Adapterframe for court-, wheel- or telescopic loaders for picking up attachments with the Euro-quick-coupling system.

Bobcat / Euro



Zettelmeyer / Euro



Hydraulic locking



INFORMATION

- Loader sided fitting for court-, wheel- and telescopic loaders
- Attachment sided: Euro-quick coupler with mechanical one-hand locking system
- Lifting capacity: 2500 kg (1500 kg for court loaders and small size tractors),
- Weight: 70-160kg (caused by differnt loader systems)

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



ADAPTERFRAME -ATTACHMENT SIDED EURO-SYSTEM

for loader from 0,5 to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Description	Part-No.
Adapter with mechanic locking	A10 OZ-95
Adapter with hydraulic locking	A10 OZ-96

② CHOOSE TYPE OF LOADER WITH QUICK COUPLER

Frontloader without Euro-coupling system	NE-02
Courtloader Weidemann (HV), Schäffer (SWH) - (max. 1,5to lift. cap.),	NG-40
Kramer KL 10.5 - (max. 1,5to lifting cap.)	NG-40
All other courtloaders with less than 1500kg lifting capacity	NE-41
Atlas E-Serie AR 42 bis AR 86, Bobcat Tele - narrow,	NG-50
Claas Scorpion, Deutz Agrovector, JCB Q-Fit, JLG,	NG-50
Kramer, Manitou MLT, Merlo ZM II (single),	NG-50
New Holland Tele, Schäffer (System Kramer),	NG-50
Terex TL 80, Zettermeyer ZL 402 (465mm Radius)	NG-50
Weidemann (HV) 1,5-2,5to lifting cap.	NG-50
Zettermeyer ZL 402 (465mm Radius) und ZL 602 (312mm Radius)	NG-50
All other wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01
Pressure limiting valve (needed for pressures above 220 bar)	DB-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)