

PRODUCT
A20-A22



YOUR ATTACHMENT SPECIALIST - www.bressel-lade.de
Send us a mail to: info@bressel-lade.de



Attachments with 3-point linkage or municipal quick coupling plate can be picked up with this adapterframe.

A20 Scorpion / 3-point CAT III



A20 Euro / 3-point CAT III



A22 Scorpion / Size 3



INFORMATION

Product A20 - Adapterframe to 3-point linkage cat. 3

- High value cat. 3 quick coupling hooks
- Adjustable distance between hooks. (from 750 to 960mm)
- Lifting capacity max. 4000 kg (on frontloaders of tractors: 2500 kg) by using of attached machines on the adapter frame is the max. allowed lifting capacity 2000kg. Distance of gravity center 500mm in front of the hooks. Stronger versions for example for wheel loaders to work with big silage forks are deliverable on request.

A22 Adapterframe for quick mount plate

- Adapterplate fitting to municipal attachments
- Lifting capacity: 2000 kg (center of gravity 500mm in front of the plate)

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



ADAPTERFRAME TO FRONT-/TAIL HYDRAULIC

for loader from 1 to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Description	Weight	Part-No.
Adapter with 3-point hitch cat. 3	110 kg	A20 OZ-A9
Adapterplate size 3	80 kg	A22 OZ-K3
Adapterplate size 5	100 kg	A22 OZ-K5

② CHOOSE TYPE OF LOADER WITH QUICK COUPLER

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Front hydraulic cat. II	NE-18
Front hydraulic cat. III	NE-19
Courtloader	NE-41
Wheel- and telescopic loaders	NE-51

③ SPECIAL EQUIPMENT

Lower ball bush adapter cat. 3/2 (per piece)	70299032
--	----------

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)
--