



Basic equipment (Euro-System)




Basic equipment (wheel loader)



Allows the higher stacking of bale for 2m more than the loader can lift.

Bale transport



INFORMATION

- Lifting height profit ca. 2000mm
- lifting capacity 1000kg
- With 2 double acting hydraulic cylinders
- Thick material main tube with welded cones
- High value full material tines, 1100mm length
- Width 1200mm with 5 cones

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



BALE ELEVATOR

for loader from 1,5 to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Tines	Weight	Part-No.
2	350 kg	B20 BS-02
3	355 kg	B20 BS-03

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Courtloader with max. 1,5to lifting capacity	NE-41
Wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Heavy duty tine 1000 mm (per piece)	N8-06
Heavy duty tine 1250 mm (per piece)	N8-07
Flapable tine tube	KZ-02
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)