

PRODUCT  
**H30**



**YOUR ATTACHMENT SPECIALIST** - [www.bressel-lade.de](http://www.bressel-lade.de)  
Send us a mail to: [info@bressel-lade.de](mailto:info@bressel-lade.de)



The box turner is made for unloading boxes with potatoes, fruits, wine or wood with its turning range of 205°.

**Special: With pallet fork tines (Euro-SW)**



**With foldable, adjustable sidetine**



**Special: With tines, complete turned**



**INFORMATION**

- Width of pallet fork carrier 1200mm
- With 1100mm foldable, adjustable sidetine for boxes 1100-1700mm width
- Rotation to left side 205°
- With 1 doubleacting hydraulic cylinder (for 3500kg lifting capacity with 2 hydraulic cylinders)
- By choosing model with 2 hydraulic cylinders are pallet fork tines form B needed. (Higher crossing heigth)
- Norm of carrier for 1500 to 2500 lifting capacity: ISO FEM II B
- Norm of carrier for 3500 kg lifting capacity: ISO FEM III B
- Changing of gravity center: +165 mm (Without quick coupler)
- The machine is delivered without pallet fork tines in the basic equipment!

For wheel- and telescopic loaders we recommend to equip all box turners with 2 cylinders.

**Free selectable colors**

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



**- Several variants available quickly!**



# BOX TURNER

for loader from 1,5 to 4tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

## ① CHOOSE PRODUCT

Lifting capacity	Norm	Cylinder	Weight	Part-No.
1500 kg	ISO FEM II	1	280 kg	H30 GN-11
2500 kg	ISO FEM II	1	290 kg	H30 GN-12
3500 kg	ISO FEM III B	2	380 kg	H30 GN-13

## ② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Fork truck ISO FEM II	AF-1A
Fork truck ISO FEM III	AF-1B
Euro-System (+40 kg)	NE-00
Frontloader without Euro-coupling system (+50 kg)	NE-02
Courtloader with max. 1,5to lifting capacity (+40 kg)	NE-41
Wheel- or telescopic loader (+70 kg)	NE-51
Excavator Lehnhoff MS03, MS08	NE-70

## ③ SPECIAL EQUIPMENT

2. hydraulic cylinder (only for ISO FEM II model, +15 kg)	ZZ-01
Turnig direction right 205° instead of left	RL-02
2 pallet fork tines ISO FEM II B, 1500kg, 1100mm (+75 kg)	TK-03
2 pallet fork tines ISO FEM II B, 2500kg, 1100mm (+108 kg)	TK-13
2 pallet fork tines ISO FEM II B, 2500kg, 1200mm (+114 kg)	TK-14
2 pallet fork tines ISO FEM III B, 3500kg, 1100mm (+150 kg)	TK-23
2 pallet fork tines ISO FEM III B, 3500kg, 1200mm (+180 kg)	TK-24
Model with mechanic adjustable downholder (indicate box dimensions, + ca. 35 kg)	MN-02
Hydraulic sideshift (200mm, + 1xDA needed, +130 kg)	HS-01
Switch valve 12V/45l in connection with sideshift	UV-09
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

## 😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)