



The box turner is made for unloading boxes with potatoes, fruits, wine or wood with its turning range of 205°.

With pallet fork tines (Euro-SW)



With foldable, adjustable sidetine



With tines, complete turned



INFORMATION

- Width of pallet fork carrier 1200mm
- With 1100mm foldable, adjustable sidetine for boxes 1100-1700mm width
- Rotation to left side 205°
- With 1 doubleacting hydraulic cylinder (for 3500kg lifting capacity with 2 hydraulic cylinders)
- By choosing model with 2 hydraulic cylinders are pallet fork tines form B needed. (Higher crossing heigth)
- Norm of carrier for 1500 to 2500 lifting capacity: ISO FEM II B
- Norm of carrier for 3500 kg lifting capacity: ISO FEM III B
- Changing of gravity center: +165 mm (Without quick coupler)
- The machine is delivered without pallet fork tines in the basic equipment!

For wheel- and telescopic loaders we recommend to equip all box turners with 2 cylinders.

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



BOX TURNER

for loader from 1,5 to 4tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

| Lifting capacity | Norm | Cylinder | Weight | Part-No. |
|------------------|---------------|----------|--------|-----------|
| 1500 kg | ISO FEM II | 1 | 280 kg | H30 GN-11 |
| 2500 kg | ISO FEM II | 1 | 290 kg | H30 GN-12 |
| 3500 kg | ISO FEM III B | 2 | 380 kg | H30 GN-13 |

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

| | |
|---|-------|
| Fork truck ISO FEM II | AF-1A |
| Fork truck ISO FEM III | AF-1B |
| Euro-System (+40 kg) | NE-00 |
| Frontloader without Euro-coupling system (+50 kg) | NE-02 |
| Courtloader with max. 1,5to lifting capacity (+40 kg) | NE-41 |
| Wheel- or telescopic loader (+70 kg) | NE-51 |

③ SPECIAL EQUIPMENT

| | |
|--|-------|
| 2. hydraulic cylinder (only for ISO FEM II model, +15 kg) | ZZ-01 |
| Turnig direction right 205° instead of left | RL-02 |
| 2 pallet fork tines ISO FEM II B, 1500kg, 1100mm (+75 kg) | TK-03 |
| 2 pallet fork tines ISO FEM II B, 2500kg, 1100mm (+108 kg) | TK-13 |
| 2 pallet fork tines ISO FEM II B, 2500kg, 1200mm (+114 kg) | TK-14 |
| 2 pallet fork tines ISO FEM III B, 3500kg, 1100mm (+150 kg) | TK-23 |
| 2 pallet fork tines ISO FEM III B, 3500kg, 1200mm (+180 kg) | TK-24 |
| Model with mechanic adjustable downholder (indicate box dimensions, + ca. 35 kg) | MN-02 |
| Hydraulic sideshift (200mm, + 1xDA needed, +130 kg) | HS-01 |
| Switch valve 12V/45l in connection with sideshift | UV-09 |
| Pressure limiting valve (needed for pressures above 220 bar) | DB-01 |
| Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.) | DH-01 |

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)