



**Basic equipment**



**Turnable knife, sideparts, reinforcements**



**Rear view**



The Bucket for bulky goods is designed for light, big volumed loading goods (wood brush, cutted grass, etc.).

**INFORMATION**

- Highwear resistant cutting edge (150x20mm, 500HB)
- Strong substructure
- Bucket depth 900mm, bucket height 750mm
- With 2 hydraulic cylinders
- With adjustable pressure limiting valve
- Opening width ca. 1250mm

Over 1900mm width we recommend one insided reinforcement for heavy duty work. For strong loaders and 2300mm width also 2.

**Free selectable colors**

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



# BUCKET FOR BULKY GOODS

for loader from 1 to 2,5tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

## ① CHOOSE PRODUCT

Width	Volume	Weight	Part-No.
1500 mm	860 l	330 kg	L93 BA-10
1700 mm	970 l	360 kg	L93 BA-12
1900 mm	1080 l	400 kg	L93 BA-14
2100 mm	1190 l	460 kg	L93 BA-16
2300 mm	1310 l	475 kg	L93 BA-18

## ② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Courtloader with max. 1,5to lifting capacity	NE-41
Wheel- and telescopic loader (max. 2,5to lifting capacity)	NE-51

## ③ SPECIAL EQUIPMENT

High wear res. substruc. and cutting edge (200x20mm, 500HB) per m.	S2-03
Sickle reinforcement in the bucket (per piece)	AU-
Sticked gravel tines (per piece)	SZ-
Protection tube	SS-01
High wear res. substruc. & screwed knife (dbl. beveled, 500HB) per m.	S2-06
Removable bucket side parts (screwed)	SH-02
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

## 😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)