



Basic equipment 1250mm



Special: Removable sideparts, reduced sickles



Special: Removable sideparts, reduced sickles



The downloader keeps loose loading material in the bucket. The downholder in standard version is not designed for heavy pulling work. (f.E. Pulling manure out of cattle stable or loading silage).

INFORMATION

- With highwear resistant cutting edge (150x16mm, 500HB)
- With strong substructure
- Bucket depth 900mm, bucket height 750mm
- Downholder with welded steel sickles
- 1000 to 1700mm width with 1 double acting hydraulic cylinder and standard sickles
- 1900 to 2100mm width with 2 double acting hydraulic cylinders and stronger sickles
- Opening width ca. 1220mm

Free selectable colors





BUCKET WITH DOWNHOLDER

for loader from 1 to 2tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Sickles	Cylinder	Volume	Weight	Part-No.
1000 mm	6	1	585 l	195 kg	L85 BA-05
1200 mm	7	1	705 l	220 kg	L85 BA-07
1300 mm	7	1	760 l	235 kg	L85 BA-08
1500 mm	8	1	880 l	270 kg	L85 BA-10
1700 mm	9	1	1000 l	295 kg	L85 BA-12
1900 mm	10	2	1110 l	340 kg	L85 BA-14
2100 mm	11	2	1230 l	365 kg	L85 BA-16

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Courtloader with max. 1,5to lifting capacity	NE-41
Wheel- or telescopic loader with max. 2tons lifting capacity	NE-51

③ SPECIAL EQUIPMENT

Downholder with 2 cylinders (1000-1700mm)	HZ-02
Stronger cutting edge 150x20mm, 500HB (per m.)	S1-02
Downholder with stronger sickles (1000-1700mm, per piece)	VS-01
Removable bucket side parts (screwed)	SH-02

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)