



This bucket can be connected quickly on the pallet forks.

Loading position



Dumped



Tipped



INFORMATION

- Individual fitted tubes for pallet fork tines (Please indicate diameter of pallet fork tines)
- With highwear resistant cutting edge (150x16mm, 500HB)
- Bucket height 800mm, Bucket depth 1300mm
- For loading goods with up to 900kg/m³
- With rounded bucket side parts
- With 1 double acting hydraulic cylinder
- Gravity center of loading goods ca. 800mm
- (Own gravity center [COG] see chart)

Free selectable colors

■ RAL 7043

■ RAL 9005

Other colors possible for an extra surcharge

■ RAL 6011

■ RAL 2011

■ Others (on request)



FORK TRUCK BUCKET -FOR TINES

for fork truck with 1,5 to 4,5to lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Volume	ca. theo.	COG	Weight	Part-No.
1100 mm	660 l	0,87 m ³	575 mm	310 kg	L30 BA-06
1300 mm	780 l	1,04 m ³	600 mm	340 kg	L30 BA-08
1400 mm	840 l	1,13 m ³	630 mm	380 kg	L30 BA-09
1600 mm	960 l	1,30 m ³	660 mm	435 kg	L30 BA-11
1800 mm	1080 l	1,46 m ³	680 mm	490 kg	L30 BA-13
2000 mm	1200 l	1,63 m ³	715 mm	540 kg	L30 BA-15

② CHOOSE PALLET FORK TINE DIAMETER

Tine diameter max. 100x50mm	GQ-01
Tine diameter max. 130x60mm	GQ-10
Tine diameter max. 150x70mm	GQ-02
Individual tine diameter (please measure)	GQ-00

③ SPECIAL EQUIPMENT

■ Color RAL 7043 - grey	FA-02
■ Color RAL 9005 - black	FA-03

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)