




Rear view



Dumped



Tipped



This attachment is connected directly to the pallet fork carrier. It has high volumes and tipping angles.

INFORMATION

- For fork lift trucks - connected to the pallet fork carrier (ISO FEM II - 407mm height of pallet fork carrier or ISO FEM III - 508mm height of pallet fork carrier)
- With highwear resistant cutting edge (150x20mm, 500HB)
- With strong substructure
- With 2 hydraulic cylinders
- Own gravity center [ESP] and gravity center of loading goods [LSP] please find in the chart

Width 1300mm: Bucket depth 1100mm, bucket height 800mm

Width 1500-2000mm: Bucket depth 1300mm, bucket height 1000mm

The width 1300mm can be used for loose materials with up to 1800kg/m³ and wider buckets for goods with up to 1300kg/m³.

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



FORK TRUCK BUCKET -UNIVERSAL

for fork truck with 1,5 to 4,5to lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Volume	ca. theo.	ESP / LSP	Weight	Part-No.
1300 mm	650 l	0,8 m ³	450/820 mm	580 kg	L33 BA-08
1500 mm	1100 l	1,35 m ³	500/900 mm	620 kg	L33 BA-10
1800 mm	1300 l	1,61 m ³	520/900 mm	680 kg	L33 BA-13
2000 mm	1450 l	1,80 m ³	530/900 mm	720 kg	L33 BA-15

② CHOOSE TYPE OF FORK CARRIER NORM

ISO FEM II	AF-1A
ISO FEM III	AF-1B
ISO FEM II and III combined	NE-32
ISO FEM IV	NE-15

③ SPECIAL EQUIPMENT

High wear res. substruc. and cutting edge (200x20mm, 500HB) per meter	S2-03
High boron screwed knife (200x20mm, dbl. beveled, 500HB) per meter	S2-06
Bucket side parts with rounded egdes	KS-01
Raised sideparts	ES-01
Quick connect locking	SH-10

😊 READY (ALL PRICES +7,5% SURCHARGE)

Lieferung im Rahmen unseres Werksverkehrs an die Fachhandelsadresse Ihrer Wahl innerhalb Deutschlands

Lieferung per Spedition zum schnellstmöglichen Termin (Kosten auf Anfrage)