



The Funnel bucket can be loaded like a normal bucket. It can be used for loose materials like grain, pellets, salt, etc. The bucket has a 300mm diameter discharge opening which can be opened and closed by hydraulic.


### Basic equipment



### Rear view



### Discharge opening



### INFORMATION

- Qualified for loading of pour loading goods like grain, pellets, salt, etc.
- Highwear resistant cutting edge (200x20mm, 500HB)
- Strong substructure
- Hydraulic discharge opening 300mm diameter (1 double acting function needed)
- **NEW DESIGN 2017:** Optimized design for easier filling procedure
- Brackets are placed deeper on the funnel (more lifting high, less risk of collision)

#### Important:

This attachment is not optimal for loader with Z-Bar cinematic.

#### Free selectable colors



RAL 7043



RAL 9005



RAL 6011



RAL 2011



# FUNNEL BUCKET

for loader from 2,5 to 8tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

## ① CHOOSE PRODUCT

Width	Depth	Height	Volume	Weight	Part-No.
1600 mm	1515 mm	1150 mm	1770 l	650 kg	L80 BA-11
2000 mm	1715 mm	1300 mm	2790 l	790 kg	L80 BA-G5
2000 mm	1815 mm	1400 mm	3190 l	830 kg	L80 BA-15

## ② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Wheel- and telescopic loader	NE-51

## ③ SPECIAL EQUIPMENT

Welded safety grid over the discharge opening	SG-01
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

## 😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)