




basic equipment (with a higher number of prongs)



Hydraulic push-off wall



Strong construction



INFORMATION

- Thick material main tubes 140x140mm with welded cones
- High value extra heavy duty tines 1400mm length (56mm Diameter)
- With 2 x heavy duty tines 1000mm length at every side
- Height of backpart 1400mm (latticed)

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



GREEN FORAGE FORK

for loader from 4,5 to 12 tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Tines	Weight	Part-No.
2420 mm	9	870 kg	D30 BA-20
2700 mm	10	920 kg	D30 BA-23
2980 mm	11	970 kg	D30 BA-26
3260 mm	12	1050 kg	D30 BA-30
3540 mm	13	1120 kg	D30 BA-32
3820 mm	14	1190 kg	D30 BA-33
4100 mm	15	1260 kg	D30 BA-35
4380 mm	16	1330 kg	D30 BA-60
4660 mm	17	1400 kg	D30 BA-61
4940 mm	18	1470 kg	D30 BA-51

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Front hydraulic cat. II	AF-3B
Front hydraulic cat. III	AF-3C
Tail hydraulic cat. IV	AF-22
Wheelloader with Z-bar Kinematic	NE-59
All other wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Hydraulic push-off wall 2420-2700mm (+ 450kg, + 1x DA.)	AW-02s
Hydraulic push-off wall 2701-3540mm (+500kg, + 1x DA.)	AW-02m
Hydraulic push-off wall 3541-4940mm (+550kg, + 1x DA.)	AW-02l
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)