



This attachment allows working with big working width. It can be folded for transport on the street. It is very strong constructed for very heavy wheel- and telescopic loaders.

Folded



Extremely strong constructed



Special: Tine protection



INFORMATION

- Thick material main tube with welded cones
- High wear resistant cutting edge (200x20mm, 500HB) as protection for the main tube
- High value full material heavy duty tines 1400mm length (56mm diameter)
- With 2 x heavy duty tines 1000mm length at every side
- Height of middle part 1400mm
- Height of side part 1200mm
- All backparts latticed
- With 2 hydraulic cylinders (both sides working together on one hydraulic function)
- With adjustable pressure hold-/ and limiting valve
- Width (folded) 2850mm



- Several variants available quickly!



GREEN FORAGE FORK - FOLDABLE

for loader from 6 to 12tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Tines	Weight	Part-No.
4250 mm	18	1550 kg	D35 BA-50
4750 mm	20	1700 kg	D35 BA-52
5250 mm	22	1850 kg	D35 BA-55

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Wheelloader with Z-bar Kinematic	NE-59
All other wheel- or telescopic loader	NE-51

Please indicate **ALWAYS** manufacturer and type of the loader on inquiries or orders!

③ SPECIAL EQUIPMENT

Description	Part-No.
■ Color RAL 7043 - grey	FA-02
■ Color RAL 9005 - black	FA-03
Protection tubes (set of 5 pieces)	SS-01
Adapterframe for 3-point-linkage cat. 3 or 4 to ISO carriage - tippable	D35K
Tine length 1000mm for D35K needed	ZL-10

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)