



**Hydraulic push-off wall**



**Rear view**



**Hydraulic push-off wall**



The Green forage grapple is an attachment for pushing silage with heavy loaders.

**INFORMATION**

- Thick material main tube with welded cones
- High value full material heavy duty tines 1400mm length (56mm diameter)
- Distance between tines 280mm
- 2 heavy duty tines 1000mm on every side
- Height of latticed backpart 1400mm
- 2 rearwards placed hydraulic cylinders
- Opening width ca. 1900mm

**Free selectable colors**

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



# GREEN FORAGE GRAPPLE

for loader from 6 to 12tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

## ① CHOOSE PRODUCT

Width	Volume	Tines	Weight	Part-No.
2420 mm	3850 l	9	1380 kg	D55 BA-20
2700 mm	4300 l	10	1500 kg	D55 BA-23
2980 mm	4750 l	11	1640 kg	D55 BA-26
3260 mm	5200 l	12	1780 kg	D55 BA-30
3540 mm	5650 l	13	1920 kg	D55 BA-32

## ② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Description	Part-No.
Tail hydraulic cat. III	AF-18
Tail hydraulic cat. IV	AF-22
Wheelloader with Z-bar Kinematic	NE-59
All other wheel- or telescopic loader	NE-51

## ③ SPECIAL EQUIPMENT

Description	Part-No.
Hydraulic push-off wall max. 2700mm width	AW-02s
Hydraulic push-off wall 2701-3540mm width	AW-02b
Switch valve 12V / 90l (without cable and switch)	UV-02
Switch valve 12V / 120l (without cable and switch)	UV-03
Switch valve 24V / 90l (without cable and switch)	UV-05
Switch valve 24V / 120l (without cable and switch)	UV-06
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

## 😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)