



Basic equipment



Special: Gravel tines



Special: Gravel tines, protection tube



For heavy duty loading goods and soil working.

INFORMATION

- Highwear resistant cutting edge (150x20mm, 500HB)
- Strong substructure
- Spill guard
- Bucket depth 1050mm, bucket height 920mm
- With 1 reinforcement from 2200 width with 2 reinforcements.

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



HEAVY DUTY BUCKET L

for loader from 2,5 to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Volume	ca. theo.	Weight	Part-No.
2000 mm	1060 l	1,32 m ³	530 kg	L27 BA-15
2200 mm	1160 l	1,45 m ³	585 kg	L27 BA-17
2300 mm	1220 l	1,53 m ³	620 kg	L27 BA-18
2400 mm	1280 l	1,60 m ³	645 kg	L27 BA-19
2500 mm	1330 l	1,67 m ³	665 kg	L27 BA-21
2600 mm	1380 l	1,73 m ³	690 kg	L27 BA-22
2800 mm	1480 l	1,86 m ³	740 kg	L27 BA-24

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Wheelloader with Z-bar Kinematic	NE-59
All other wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

High wear res. substruc. and cutting edge (200x20mm, 500HB) per meter	S2-03
Graveltine -sticked (per piece)	SZ-
High wear res. substruc. and cutting edge (300x30mm, 500HB) per meter	S2-05
Graveltine -sticked HD for 30mm strong knife (per piece)	SZ-s
Protection tube	SS-01
High boron screwed knife (200x20mm, dbl. beveled, 500HB) per meter	S2-06
Rearwards cutting edge for dozing work -per meter	GS-01

😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)