



Basic equipment



With protection tube



Rearwards cutting edge



For heavy duty loading goods and soil working.

INFORMATION

- Highwear resistant cutting edge (150x20mm, 500HB)
- Strong substructure
- Spill guard
- Bucket depth 750mm, bucket height 600mm

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



HEAVY DUTY BUCKET S

for loader from 0,5 to 2tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Volume	ca. theo.	Weight	Part-No.
900 mm	210 l	0,27 m ³	130 kg	L25 BA-03
1000 mm	235 l	0,30 m ³	145 kg	L25 BA-05
1100 mm	255 l	0,33 m ³	160 kg	L25 BA-06
1200 mm	280 l	0,36 m ³	175 kg	L25 BA-07
1300 mm	300 l	0,39 m ³	190 kg	L25 BA-08
1400 mm	325 l	0,42 m ³	205 kg	L25 BA-09
1500 mm	350 l	0,46 m ³	220 kg	L25 BA-10
1600 mm	370 l	0,49 m ³	235 kg	L25 BA-11

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Courtloader with max. 1,5to lifting capacity	NE-41
Wheel- or telescopic loader with max. 2,0to lifting capacity	NE-51

③ SPECIAL EQUIPMENT

Graveltine -screwed (per piece)	SZ-
Protection tube	SS-01
Rearwards cutting edge for dozing work (per m.)	GS-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)