



Rear view



Dimensions



The Heavy duty bucket XL is optimal for loaders with ISO 23727 (System Volvo) quick coupler.

Sticked gravel tine HD



INFORMATION

- Made for wheel loader with ISO 23727 quickcoupler
- Highwear resistant cutting edge (300x30mm, 500HB)
- Highwear resistant substructure
- Bucket depth 1100mm, bucket height 1100mm (with spill guard 1375mm)

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



HEAVY DUTY BUCKET XL

for loader from 5 to 10tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Volume	ca. theo.	Weight	Part-No.
2300 mm	1725 l	2,2 m ³	1005 kg	L29 BA-18
2400 mm	1800 l	2,3 m ³	1035 kg	L29 BA-19
2500 mm	1875 l	2,4 m ³	1065 kg	L29 BA-21
2600 mm	1950 l	2,5 m ³	1095 kg	L29 BA-22
2800 mm	2100 l	2,7 m ³	1155 kg	L29 BA-24
2900 mm	2175 l	2,8 m ³	1185 kg	L29 BA-25

② CHOOSE TYPE OF LOADER WITH ISO 23727 BRACKETS

Wheelloader with ISO 23727 carriage and Z-bar Kinematic

All other wheel loader with ISO 23727 carriage

③ SPECIAL EQUIPMENT

Graveltine HD -sticked (per piece)

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)