



Rear view



Dimensions



The Heavy duty bucket XL is optimal for loaders with ISO 23727 (System Volvo) quick coupler.

Special: Sticked gravel tine HD



INFORMATION

- Made for wheel loader with ISO 23727 quickcoupler (locking hole approx. 270mm over ground fitting also for many loaders with big agri-tires)
- Highwear resistant cutting edge (300x30mm, 500HB)
- Highwear resistant substructure
- Bucket depth 1100mm, bucket height 1100mm (with spill guard 1375mm)

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



HEAVY DUTY BUCKET XL

for loader from 5 to 10tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

| Width | Volume | ca. theo. | Weight | Part-No. |
|---------|--------|--------------------|---------|-----------|
| 2300 mm | 1725 l | 2,2 m ³ | 1005 kg | L29 BA-18 |
| 2400 mm | 1800 l | 2,3 m ³ | 1035 kg | L29 BA-19 |
| 2500 mm | 1875 l | 2,4 m ³ | 1065 kg | L29 BA-21 |
| 2600 mm | 1950 l | 2,5 m ³ | 1095 kg | L29 BA-22 |
| 2800 mm | 2100 l | 2,7 m ³ | 1155 kg | L29 BA-24 |
| 2900 mm | 2175 l | 2,8 m ³ | 1185 kg | L29 BA-25 |

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

| | |
|---|-------|
| Wheelloader with ISO 23727 carriage and Z-bar Kinematic | NE-59 |
| All other wheel loader with ISO 23727 carriage | NE-51 |

③ SPECIAL EQUIPMENT

| | |
|------------------------------------|-------|
| Graveltine HD -sticked (per piece) | SZ-s |
| Protection tube | SS-01 |

😊 READY (ALL PRICES +7,5% SURCHARGE)

| |
|--|
| Delivery FCA at factory Visselhövede (Transportcosts on request) |
|--|