

PRODUCT
L70-L71



YOUR ATTACHMENT SPECIALIST - www.bressel-lade.de
Send us a mail to: info@bressel-lade.de



A High tip bucket raises the unload height and the dumping angle.

Type XXL



Type XXL with raised side parts



Type XL rear view



INFORMATION

- Qualified for loading of pour loading goods with max. 1000kg/m³
- With highwear resistant substructure and cutting edge (300x30mm, 500HB)
- With 2 hydraulic cylinders (Max. hydraulic pressure 220 bar)
- ca. 100° tipping angle

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



HIGH TIP BUCKET XL / XXL

for loader from 4to 8tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Type / width / prod	Depth / height	Volume (ca. theo.)	Weight	Part-No.
XL / 2400 mm / [L70]	1500 mm / 1300mm	2440 l / 3,1 m ³	1320 kg	L70 BA-19
XL / 2600 mm / [L70]	1500 mm / 1300mm	2650 l / 3,3 m ³	1420 kg	L70 BA-22
XL / 2800 mm / [L70]	1500 mm / 1300mm	2860 l / 3,6 m ³	1520 kg	L70 BA-24
XL / 3000 mm / [L70]	1500 mm / 1300mm	3070 l / 3,9 m ³	1620 kg	L70 BA-27
XXL / 2600 mm / [L71]	1800 mm / 1500mm	3700 l / 4,6 m ³	1900 kg	L71 BA-22
XXL / 2800 mm / [L71]	1800 mm / 1500mm	4000 l / 5,0 m ³	2000 kg	L71 BA-24
XXL / 3000 mm / [L71]	1800 mm / 1500mm	4300 l / 5,4 m ³	2100 kg	L71 BA-27

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Wheelloader with Z-bar Kinematic	NE-59
All other wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Screwed knife (dbl. beveled, 250x25mm, 500HB) per m.	S5-20
Raised sideparts	SH-05
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)