

PRODUCT  
**L10-L11**



**YOUR ATTACHMENT SPECIALIST** - [www.bressel-lade.de](http://www.bressel-lade.de)  
Send us a mail to: [info@bressel-lade.de](mailto:info@bressel-lade.de)



Designed for loose loading goods in agriculture branch.


**Basic equipment**



**Back view - Euro-System**



**Special: PU-Edge, rounded edge, reinforcements**



**INFORMATION**

- Bucket depth 900mm, bucket height 750mm
- With highwear resistant cutting edge (150x16mm, 500HB)
- With strong substructure
- For loose loading goods with up to 900kg/m<sup>3</sup>

We recommend the sickle reinforcement for universal usage on width above 2200mm and 2 of them on width above 2400mm.

**Free selectable colors**

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



**- Several variants available quickly!**



# LIGHT MATERIAL BUCKET

for loader from 0,5 to 2,5tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

## ① CHOOSE PRODUCT

| Width [Product] | Volume | ca. theo.           | Weight | Part-No.  |
|-----------------|--------|---------------------|--------|-----------|
| 900 mm [L10]    | 350 l  | 0,43 m <sup>3</sup> | 135 kg | L10 BA-03 |
| 1000 mm [L10]   | 390 l  | 0,48 m <sup>3</sup> | 150 kg | L10 BA-05 |
| 1100 mm [L10]   | 430 l  | 0,53 m <sup>3</sup> | 165 kg | L10 BA-06 |
| 1200 mm [L10]   | 465 l  | 0,57 m <sup>3</sup> | 180 kg | L10 BA-07 |
| 1300 mm [L10]   | 500 l  | 0,62 m <sup>3</sup> | 195 kg | L10 BA-08 |
| 1400 mm [L10]   | 540 l  | 0,66 m <sup>3</sup> | 210 kg | L10 BA-09 |
| 1500 mm [L10]   | 580 l  | 0,72 m <sup>3</sup> | 225 kg | L10 BA-10 |
| 1600 mm [L10]   | 620 l  | 0,77 m <sup>3</sup> | 240 kg | L10 BA-11 |
| 1800 mm [L10]   | 700 l  | 0,87 m <sup>3</sup> | 260 kg | L10 BA-13 |
| 2000 mm [L11]   | 775 l  | 0,96 m <sup>3</sup> | 280 kg | L11 BA-15 |
| 2200 mm [L11]   | 850 l  | 1,05 m <sup>3</sup> | 300 kg | L11 BA-17 |
| 2400 mm [L11]   | 930 l  | 1,16 m <sup>3</sup> | 335 kg | L11 BA-19 |
| 2500 mm [L11]   | 970 l  | 1,21 m <sup>3</sup> | 345 kg | L11 BA-21 |
| 2600 mm [L11]   | 1010 l | 1,26 m <sup>3</sup> | 355 kg | L11 BA-22 |

## ② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

|  |       |
|--|-------|
| Euro-System (min. 1200mm width)                              | AF-M4 |
| Frontloader without Euro-coupling system                     | NE-02 |
| Courtloader with max. 1,5to lifting capacity                 | NE-41 |
| Wheel- or telescopic loader with max. 2,5to lifting capacity | NE-51 |

## ③ CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

|   |       |
|---|-------|
| One sickle reinforcement                                    | AU-02 |
| Two sickle reinforcements                                   | AU-03 |
| Polyurethane cutting edge (for sensitiv grounds) -per meter | S1-07 |
| Stronger cutting edge 200x20mm, 500 HB - per meter          | S1-03 |
| Screwed knife (dbl. beveled, 200x20mm, 500HB) per meter     | S1-06 |
| Rounded bucket side parts (for sensitive loading goods)     | KS-01 |
| Raised bucket side parts                                    | SH-05 |

## 😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)