



Standard 3000mm
[W20]mit rubber (special)



Profi - 6000mm



The maize pushing blades (PROFI-Models) can be used for the heaviest and strongest traktors.



INFORMATION

· Blade with reinforced body

Model: STANDARD [W20]

- 1000mm height, 300mm long sideparts
- Recommended for tractors with up to 180 hp

Model: PROFI [W21]

- Height: 1400mm, 600mm long sideparts
- With screwed cutting edge out of hardened steel 150x20mm, 500HB

Model: PROFI - foldable [W22]

- Each sidepart swivable, 2 doubleacting hydraulic functions needed
- Working range: 90° backwards and 45° to the front
- Width folded: 2850mm
- With screwed cutting edge out of hardened steel 150x20mm, 500HB



MAIZE PUSHING BLADE

for loader from 2,0 to 10tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS 0 + 2 + 3 = 3

O CHOOSE PRODUCT			
Width	Model [Product]	Weight	Part-No.
2200 mm	Standard [W20]	275 kg	W20 BA-17
2500 mm	Standard [W20]	315 kg	W20 BA-21
3000 mm	Standard [W20]	385 kg	W20 BA-27
2750 mm	Profi [W21]	750 kg	W21 BA-C3
3000 mm	Profi [W21]	820 kg	W21 BA-27
3500 mm	Profi [W21]	960 kg	W21 BA-31
4000 mm	Profi - Turnable [W22]	1100 kg	W22 BA-34
5000 mm	Profi - Turnable [W22]	1250 kg	W22 BA-54
6000 mm	Profi - Turnable [W22]	1400 kg	W22 BA-57

2 LOADER QUICK COUPLER (INDICATE BRAND & TYPE)		
Euro-System	AF-M4	
Frontloader without Euro-coupling system	NE-02	
Front hydraulic cat. II	NE-18	
Front hydraulic cat. III	NE-19	
Front hydraulic cat. IV	NE-24	
Euro-System in connection with front cat. II	NE-20	
Euro-System in connection with front cat. III	NE-21	
Wheel- and telescopic loader	NE-51	
Please indicate ALWAYS manufacturer and type of the loader on inquiries or orders!		

SPECIAL EQUIPMENT	
Color RAL 7043 - grey	FA-02
Color RAL 9005 - black	FA-03
Pressure limiting valves (needed for pressures above 220 bar)	DB-01

⊕ READY	
Delivery FCA at factory Visselhövede (Transportcosts on request)	