

PRODUCT
W20-W22



YOUR ATTACHMENT SPECIALIST - www.bressel-lade.de
Send us a mail to: info@bressel-lade.de



Standard 3000mm
[W20]mit rubber (special)



Profi - 6000mm



Profi - 6000 mm



The maize pushing blades (PROFI-Models) can be used for the heaviest and strongest tractors.

INFORMATION

- Blade with reinforced body
- Model: STANDARD [W20]**
- 1000mm height, 300mm long sideparts
- Recommended for tractors with up to 180 hp
- Model: PROFI [W21]**
- Height: 1400mm, 600mm long sideparts
- With screwed cutting edge out of hardened steel 150x20mm, 500HB
- Model: PROFI - foldable [W22]**
- Each sidepart swivable, 2 doubleacting hydraulic functions needed
- Working range: 90° backwards and 45° to the front
- Width folded: 2850mm
- With screwed cutting edge out of hardened steel 150x20mm, 500HB

Free selectable colors



RAL 7043



RAL 9005



RAL 6011



RAL 2011



MAIZE PUSHING BLADE

for loader from 2,0 to 10tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Model [Product]	Weight	Part-No.
2200 mm	Standard [W20]	275 kg	W20 BA-17
2500 mm	Standard [W20]	315 kg	W20 BA-21
3000 mm	Standard [W20]	385 kg	W20 BA-27
2750 mm	Profi [W21]	750 kg	W21 BA-C3
3000 mm	Profi [W21]	820 kg	W21 BA-27
3500 mm	Profi [W21]	960 kg	W21 BA-31
4000 mm	Profi - Turnable [W22]	1100 kg	W22 BA-34
5000 mm	Profi - Turnable [W22]	1250 kg	W22 BA-54
6000 mm	Profi - Turnable [W22]	1400 kg	W22 BA-57

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Front hydraulic cat. II	NE-18
Front hydraulic cat. III	NE-19
Front hydraulic cat. IV	NE-24
Euro-System in connection with front cat. II	NE-20
Euro-System in connection with front cat. III	NE-21
Wheel- and telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Pressure limiting valves (needed for pressures above 220 bar)	DB-01
---	-------

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)