

PRODUCT
W20-W22



YOUR ATTACHMENT SPECIALIST - www.bressel-lade.de

Send us a mail to: info@bressel-lade.de



The maize pushing blades (PROFI-Models) can be used for the heaviest and strongest tractors.

INFORMATION

- Blade with reinforced body
- Model: STANDARD [W20]**
- 1000mm height, 300mm long sideparts
- Recommended for tractors with up to 180 hp
- Model: PROFI [W21]**
- Height: 1400mm, 600mm long sideparts
- With screwed cutting edge out of hardened steel 150x20mm, 500HB
- Model: PROFI - foldable [W22]**
- Each sidepart swivable, 2 doubleacting hydraulic functions needed
- Working range: 90° backwards and 45° to the front
- Width folded: 2850mm
- With screwed cutting edge out of hardened steel 150x20mm, 500HB

Free selectable colors





MAIZE PUSHING BLADE

for loader from 2,0 to 10tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Model [Product]	Weight	Part-No.
2200 mm	Standard [W20]	275 kg	W20 BA-17
2500 mm	Standard [W20]	315 kg	W20 BA-21
3000 mm	Standard [W20]	385 kg	W20 BA-27
2750 mm	Profi [W21]	750 kg	W21 BA-C3
3000 mm	Profi [W21]	820 kg	W21 BA-27
3500 mm	Profi [W21]	960 kg	W21 BA-31
4000 mm	Profi - Turnable [W22]	1100 kg	W22 BA-34
5000 mm	Profi - Turnable [W22]	1250 kg	W22 BA-54
6000 mm	Profi - Turnable [W22]	1400 kg	W22 BA-57

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Front hydraulic cat. II	NE-18
Front hydraulic cat. III	NE-19
Front hydraulic cat. IV	NE-24
Euro-System in connection with front cat. II	NE-20
Euro-System in connection with front cat. III	NE-21
Wheel- and telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Pressure limiting valves (needed for pressures above 220 bar)	DB-01
---	-------

😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)
--