



The Manure Bucket is heavy duty designed for loading manure. By removing the screwed sideparts it is easier to load heavy manure.

Basic equipment



Basic equipment



Removed sideparts



INFORMATION

- With highwear resistant cutting edge (150x20mm, 500HB)
- With strong substructure
- Bucket depth 1000mm, Bucket height 800mm
- With 1 respectively 2 sickle reinforcements
- With removable sideparts (screwed)
- With 2 hydraulic cylinders
- Opening width ca. 1450mm
- Thick material main tube with welded cones
- Twist protected tines with 800mm length in the grapple



MANURE BUCKET

for loader from 2,5to 5,5tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Tines	Volume	Weight	Part-No.
1600 mm	7	1130 l	640 kg	L90 BA-11
1800 mm	8	1280 l	660 kg	L90 BA-13
2000 mm	9	1420 l	680 kg	L90 BA-15
2200 mm	10	1560 l	700 kg	L90 BA-17
2400 mm	10	1700 l	720 kg	L90 BA-19
2600 mm	11	1840 l	740 kg	L90 BA-22

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Wheel- or telescopic loader	NE-51
Please indicate ALWAYS manufacturer and type of the loader on inquiries or orders!	

③ SPECIAL EQUIPMENT

■ Color RAL 7043 - grey	FA-02
■ Color RAL 9005 - black	FA-03
With 1 bowed tine 600mm at every side	ZS-01
High boron cutting edge (200x20mm, 500HB) -per Meter	S2-03
High boron screwed knife (200x20mm, dbl. beveled, 500HB) -per Meter	S2-06
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)
--