



Used for loading manure or pushing silage.

**Standard equipment**



**Ready to work with bracket**



**Reinforcement bush**



**INFORMATION**

- Thick material main tube with welded cones and reinforcement bushes
- High value full material heavy duty tines, 1000mm length
- Height 780mm

**Free selectable colors**

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



# MANURE FORK L

for loader from 2,0 to 4,5tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

## ① CHOOSE PRODUCT

Width	Tines	Weight	Part-No.
1700 mm	9	280 kg	D15 BA-12
1900 mm	10	310 kg	D15 BA-14
2100 mm	11	340 kg	D15 BA-16
2300 mm	12	370 kg	D15 BA-18
2500 mm	13	400 kg	D15 BA-21
2700 mm	14	430 kg	D15 BA-23

## ② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Wheel- or telescopic loader	NE-51

## ③ SPECIAL EQUIPMENT

Heavy duty tine 1250 mm (per piece)	N8-07
Heavy duty tine 1400 mm (per piece)	N8-08
Hydraulic push-off wall < 1900mm width (+190kg, + 1x DA.)	AW-02s
Hydraulic push-off wall >1900mm width (+210kg, + 1x DA.)	AW-02b
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

## 😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)