



Used for loading manure or pushing silage.

Standard equipment



Hydraulic push-off wall



Rear view



INFORMATION

- Thick material main tube with welded cones and reinforcement bushes
- High value full material tines, 800mm length
- Height 750mm

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



MANURE FORK M

for loader from 0,5 to 2,5tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Tines	Weight	Part-No.
900 mm	5	95 kg	D10 BA-03
980 mm	6	100 kg	D10 BA-04
1200 mm	7	125 kg	D10 BA-07
1300 mm	7	135 kg	D10 BA-08
1500 mm	8	155 kg	D10 BA-10
1700 mm	9	170 kg	D10 BA-12
1900 mm	10	195 kg	D10 BA-14
2100 mm	11	215 kg	D10 BA-16
2300 mm	12	235 kg	D10 BA-18
2500 mm	13	255 kg	D10 BA-21

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System (min. 1200mm width)	AF-M4
Frontloader without Euro-coupling system	NE-02
Courtloader with max. 1,5to lifting capacity	NE-41
Wheel- or telescopic loader with max. 2,5to lifting capacity	NE-51

③ SPECIAL EQUIPMENT

Longer tines 1000mm (per tine)	N8-03
Longer tines 1100mm (per tine)	N8-04
Heavy duty tines 800mm (per tine)	N8-05
Heavy duty tines 1000mm (per tine)	N8-06
Hydraulic push-off wall <1900mm width (+170kg, + 1x DA.)	AW-02s
Hydraulic push-off wall >1900mm width (+190kg, + 1x DA.)	AW-02b
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)