



Opened



With gravel tines



Gravel tines with protection tube



The multipurpose bucket offers a lot of applications: Loading, like with a normal bucket, unloading / dispensing without dumping the bucket, dozing work with opened bucket, collection of rest material, grabbing of f.e. curbs

INFORMATION

- Highwear resistant cutting edge (150x20mm, 500HB)
- Bucket depth 650mm, bucket height 750mm
- Spill guard
- 2 hydraulic cylinders with 45l/min oil flow divider (Max. hydraulic pressure 220 bar)
- Opening width ca. 670mm

IMPORTANT: The smallest possible working width of the attachment must be 450mm wider than the width of the quick coupling frame of the loader.

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



MULTI PURPOSE BUCKET S (4 IN 1)

for loader from 1 to 5,5tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Volume	ca. theo.	Weight	Part-No.
1200 mm	290 l	0,35 m ³	320 kg	L55 BA-07
1300 mm	310 l	0,37 m ³	335 kg	L55 BA-08
1400 mm	335 l	0,40 m ³	350 kg	L55 BA-09
1500 mm	360 l	0,43 m ³	365 kg	L55 BA-10
1600 mm	380 l	0,46 m ³	370 kg	L55 BA-11
1800 mm	430 l	0,52 m ³	400 kg	L55 BA-13
2100 mm	500 l	0,61 m ³	450 kg	L55 BA-16
2300 mm	550 l	0,67 m ³	500 kg	L55 BA-18
2400 mm	575 l	0,70 m ³	525 kg	L55 BA-19
2500 mm	600 l	0,73 m ³	550 kg	L55 BA-21

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System (min. 1600mm, central locking needed)	AF-M4
Frontloader without Euro-coupling system	NE-02
Courtloader with max. 1,5to lifting capacity	NE-41
Wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Sticked gravel tines (per piece)	SZ-
Protection tube	SS-01
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)