



The pallet fork is designed for loading goods on pallets. The high value pallet fork tines are adjustable in the distance to each other.

**Bobcat**



**Special: Side shift**



**Pallet fork carrier without tines**



**INFORMATION**

- With 2 forged pallet fork tines (mech. adjustable)
- The version "Without tines" is a pallet fork carrier without pallet fork tines
- Width of pallet fork carrier 1200mm (wider model deliverable)
- Fork produced acc. ISO 2330 and ISO 2328
- Lifting capacity by center of gravity: ISO 2/3 = 500mm, ISO 4 = 600mm
- Foldable forks deliverable on request !

**Free selectable colors**

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



**- Several variants available quickly!**



# PALLET FORK

for loader from 1,5 to 6tons lifting capacity

**A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊**

## ① CHOOSE PRODUCT

Tine length	Lifting cap.	Norm	Tine diameter	Weight	Part-No.
Without tines	1500 kg	DIN FEM II	n/a	80 kg	H11 TK-00
900 mm	1500 kg	DIN FEM II	80 x 35 mm	145 kg	H10 TK-01
1000 mm	1500 kg	DIN FEM II	80 x 35 mm	150 kg	H10 TK-02
1100 mm	1500 kg	DIN FEM II	80 x 35 mm	155 kg	H10 TK-03
1200 mm	1500 kg	DIN FEM II	80 x 35 mm	160 kg	H10 TK-04
1300 mm	1500 kg	DIN FEM II	80 x 35 mm	165 kg	H10 TK-05
Without tines	2500 kg	ISO FEM II B	n/a	80 kg	H11 TK-10
900 mm	2500 kg	ISO FEM II B	100 x 40 mm	180 kg	H10 TK-11
1000 mm	2500 kg	ISO FEM II B	100 x 40 mm	185 kg	H10 TK-12
1100 mm	2500 kg	ISO FEM II B	100 x 40 mm	195 kg	H10 TK-13
1200 mm	2500 kg	ISO FEM II B	100 x 40 mm	200 kg	H10 TK-14
1300 mm	2500 kg	ISO FEM II B	100 x 40 mm	205 kg	H10 TK-15
1500 mm	2500 kg	ISO FEM II B	100 x 40 mm	215 kg	H10 TK-16
1800 mm	2500 kg	ISO FEM II B	100 x 40 mm	235 kg	H10 TK-17
Without tines	4500 kg	ISO FEM III B	n/a	140 kg	H11 TK-20
900 mm	3500 kg	ISO FEM III B	100 x 50 mm	280 kg	H10 TK-21
1000 mm	3500 kg	ISO FEM III B	100 x 50 mm	285 kg	H10 TK-22
1100 mm	3500 kg	ISO FEM III B	100 x 50 mm	290 kg	H10 TK-23
1200 mm	4500 kg	ISO FEM III B	120 x 50 mm	330 kg	H10 TK-24
1300 mm	3500 kg	ISO FEM III B	100 x 50 mm	310 kg	H10 TK-25
1500 mm	4500 kg	ISO FEM III B	120 x 50 mm	360 kg	H10 TK-26
1800 mm	4500 kg	ISO FEM III B	120 x 50 mm	410 kg	H10 TK-27
Without tines	6000 kg	ISO FEM IV B	n/a	200 kg	H11 TK-40
1200 mm	6000 kg	ISO FEM IV B	130 x 60 mm	455 kg	H10 TK-42
1500 mm	6000 kg	ISO FEM IV B	130 x 60 mm	490 kg	H10 TK-45

## ② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Courtloader with max. 1,5to lifting capacity	NE-41
Wheel- or telescopic loader	NE-51
Excavator Lehnhoff MS01, MS03, MS08	NE-70

## ③ SPECIAL EQUIPMENT

Wider pallet fork carrier (max. 1500mm wide)	GT-
Wider pallet fork carrier (more than 1500mm wide, per 100mm)	GT-
<b>Side shift and other additional (see product H60-H68)</b>	

## 😊 READY (ALL PRICES +7,5% SURCHARGE)