

PRODUCT
H20-H22



YOUR ATTACHMENT SPECIALIST - www.bressel-lade.de

Send us a mail to: info@bressel-lade.de



Rear view



Side shift, swich valve



Side shift, swich valve



The pallet fork is designed for loading goods on pallets. The high value pallet fork tines are adjustable by hydraulic in the distance to each other. This function works synchron, ensured by oil flow dividers. Please note: It is not possible and allowed to grab or clamp materials between the tines.

INFORMATION

- 2 forged pallet fork tines
- Synchron working tine adjustment
- Width over all (standard model):
 - 2500kg lifting capacity ISO FEM II B = 1410 mm
 - 3500-4500kg lifting capacity ISO FEM III B = 1450 mm
 - 6000kg lifting capacity ISO FEM IV B = 1510 mm

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



PALLET FORK WITH HYDR. TINE ADJUSTMENT

for loader from 1,5 to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Tine length	Lifting capacity	Norm	Range (mi-mi)	Weight	Part-No.
900 mm	2500 kg	ISO FEM II B	170 - 1065 mm	320 kg	H20 ZL-09
1000 mm	2500 kg	ISO FEM II B	170 - 1065 mm	325 kg	H20 ZL-10
1100 mm	2500 kg	ISO FEM II B	170 - 1065 mm	330 kg	H20 ZL-11
1200 mm	2500 kg	ISO FEM II B	170 - 1065 mm	335 kg	H20 ZL-12
1300 mm	2500 kg	ISO FEM II B	170 - 1065 mm	345 kg	H20 ZL-13
900 mm	3500 kg	ISO FEM III B	190 - 1045 mm	440 kg	H21 ZL-09
1000 mm	3500 kg	ISO FEM III B	190 - 1045 mm	450 kg	H21 ZL-10
1100 mm	3500 kg	ISO FEM III B	190 - 1045 mm	455 kg	H21 ZL-11
1200 mm	4500 kg	ISO FEM III B	190 - 1045 mm	495 kg	H21 ZL-12
1300 mm	3500 kg	ISO FEM III B	190 - 1045 mm	475 kg	H21 ZL-13
1200 mm	6000 kg	ISO FEM IV B	210 - 1025 mm	705 kg	H22 ZL-12

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Courtloader with max. 1,5to lifting capacity	NE-18
Wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Wider model ISO FEM II (adjustable range 370-1355mm)	BV-21
Wider model ISO FEM III (adjustable range 350-1335mm)	BV-31
Wider model ISO FEM IV (adjustable range 330-1315mm)	BV-41
Hydraulic sideshift (200mm, + 150kg, + 1 DA func. needed)	HS-01
Swich valve 12V/45l in connection with hydr. sideshift	UV-09
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)